

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



-i biztonsági adatlap. 2/2/2024, ellenőrzés 4

1. SZAKASZ: Az anyag/keverék és a vállalat/vállalkozás azonosítása

1.1. Termékanazonosító

A készítmény azonosítása:

Kereskedelmi név: COCKPIT CLEANER High Gloss Scented Ocean SPRAY
Kereskedelmi kód: 32010

1.2. Az anyag vagy keverék megfelelő azonosított felhasználásai, illetve ellenjavallt felhasználásai
Javasolt felhasználási mód:

műszerfal tisztító

1.3. A biztonsági adatlap szállítójának adatai

Szállító:

Arexons S.p.A.
via Antica di Cassano, 23, 20063
Cernusco sul Naviglio (MI), Italy
Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

A biztonsági adatlapért felelős illetékes személy:

arexons@arexons.it

1.4. Sürgösségi telefonszám

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Egészségügyi Toxikológiai Tájékoztató Szolgálat' (ETTSz) +36-80-20-11-99 (0-24 órában,
díjmentesen hívható – csak Magyarországról)

2. SZAKASZ: A veszély azonosítása

2.1. Az anyag vagy keverék osztályozása

EC 1272/2008 (CLP) irányelv kritériumai:

- ⚠️ Veszély, Aerosols 1, Rendkívül tűzveszélyes aeroszol. Az edényben túlnyomás uralkodik: hő hatására megrepedhet.
- ⚠️ Figyelem, Eye Irrit. 2, Súlyos szemirritációt okoz.
- ⚠️ Figyelem, Skin Irrit. 2, Bőrirritáló hatású.
- ⚠️ Figyelem, STOT SE 3, Álmosságot vagy szédülést okozhat.

Aquatic Chronic 3, Ártalmas a vízi élővilágra, hosszan tartó károsodást okoz.

Az emberi egészségre és a környezetre káros fizikokémiai hatások:

Egyéb veszélyek nincsenek

2.2. Címkezési elemek

Veszélyt jelző piktogramok:



Veszély

Figyelmeztető mondatok:

H222, H229 Rendkívül tűzveszélyes aeroszol. Az edényben túlnyomás uralkodik: hő hatására megrepedhet.

H319 Súlyos szemirritációt okoz.

H315 Bőrirritáló hatású.

H336 Álmosságot vagy szédülést okozhat.

H412 Ártalmas a vízi élővilágra, hosszan tartó károsodást okoz.

Óvintézkedésre vonatkozó mondatok:

P101 Orvosi tanácsadás esetén tartsa kéznél a termék edényét vagy címkkéjét.

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



P102 Gyermekektől elzárva tartandó.

P103 Olvassa el figyelmesen és kövesse az összes utasítást.

P210 Hőtől, forró felületektől, szikrától, nyílt lángtól és más gyújtóforrástól távol tartandó. Tilos a dohányzás.

P211 Tilos nyílt lángra vagy más gyújtóforrásra permetezni.

P251 Ne lyukassza ki vagy égesse el, még használat után sem.

P271 Kizárolag szabadban vagy jól szellőző helyiségben használható.

P405 Elzárva tárolandó.

P410+P412 Napfénytől védendő. Nem érheti 50 °C/122 °F hőmérsékletet meghaladó hő.

P501 A tartalom/edény elhelyezése hulladékként a hatályos szabályozásoknak megfelelően.

Különleges utasítások:

Semmi

Tartalmaz

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
propán-2-ol; izopropil-alkohol; izopropanol

Különleges intézkedések a többször módosított REACH rendelet XVII. mellékletének megfelelően:

Semmi

Az Európai Parlament és a Tanács 648/2004/EK rendelete (a mosó- és tisztítószerekről).

A termék tartalma:

Alifás szénhidrogének

> 30 %

A termék tartalmaz még:

Illatanyagok

Allergének

d-limonene

2.3. Egyéb veszélyek

Nincs jelen PBT, vPvB vagy endokrin károsító anyag 0,1%-nál nagyobb koncentrációban.

Egyéb veszélyek:

Egyéb veszélyek nincsenek

3. SZAKASZ: Összetétel/összetevőkre vonatkozó információk

3.1. Anyagok

N.A.

3.2. Keverékek

A CLP rendelet és a vonatkozó osztályozás értelmében veszélyesnek minősülő összetevők:

>= 70% - < 80%	Szénhidrogének, C3-4; Ásványolaj gáz	Index szám: 649-199-00-1 CAS: 68476-40-4 EC: 270-681-9 REACH No.: 01-2119486557-22	◆ 2.2/1A Flam. Gas 1A H220 ◆ 2.5/L Press Gas (Liq.) H280 DECLK (CLP)*
>= 20% - < 25%	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EC: 927-510-4 REACH No.: 01-2119475515-33	◆ 2.6/2 Flam. Liq. 2 H225 ◆ 3.10/1 Asp. Tox. 1 H304 ◆ 3.2/2 Skin Irrit. 2 H315 ◆ 3.8/3 STOT SE 3 H336 ◆ 4.1/C2 Aquatic Chronic 2 H411 EUH066
>= 2% - < 3%	propán-2-ol; izopropil-alkohol; izopropanol	Index szám: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH No.: 01-2119457558-25	◆ 2.6/2 Flam. Liq. 2 H225 ◆ 3.3/2 Eye Irrit. 2 H319 ◆ 3.8/3 STOT SE 3 H336

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



332 ppb	DYPHENYL OXYDE	CAS: 101-84-8 EC: 202-981-2 REACH No.: 01-2119472545-33	3.3/2 Eye Irrit. 2 H319 4.1/A1 Aquatic Acute 1 H400 4.1/C3 Aquatic Chronic 3 H412
<1 ppb	Toluene	CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	2.6/2 Flam. Liq. 2 H225 3.8/3 STOT SE 3 H336 3.10/1 Asp. Tox. 1 H304 3.2/2 Skin Irrit. 2 H315 3.7/2 Repr. 2 H361 3.9/2 STOT RE 2 H373
<1 ppb	p-krezol	Index szám: 604-004-00-9 CAS: 106-44-5 EC: 203-398-6 REACH No.: 01-2119448336-36	3.1/3/Dermal Acute Tox. 3 H311 4.1/C3 Aquatic Chronic 3 H412 3.1/3/Oral Acute Tox. 3 H301 3.2/1B Skin Corr. 1B H314

*DECLK (CLP): Az anyag az 1272/200/EK rendelet VI. melléklet K megjegyzésének megfelelően kerül besorolásra. A rákkeltőként vagy mutagénként való harmonizált besorolás alkalmazandó, kivéve, ha kimutatható, hogy az anyag 0,1 tömegszázaléknál kevesebb 1,3-butadién (EINECS-szám: 203-450-8) tartalmaz, amely esetben az e rendelet II. címe szerinti osztályozást ezekre a veszélyességi osztályokra is el kell végezni. Ha az anyag nincs rákkeltőként vagy mutagénként besorolva, legalább a (P102)-P210-P403 óvintézkedésre vonatkozó mondatokat szerepeltetni kell.

4. SZAKASZ: Elsősegély-nyújtási intézkedések

4.1. Az elsősegély-nyújtási intézkedések ismertetése

Bőrrel való érintkezés esetén:

A szennyezett ruhaneműt azonnal le kell venni.

Azonnal bő folyóvízzel és esetleg szappannal le kell mosni azt a testrészt, amely érintkezett a termékkel.

Mossuk le teljesen a testet (zuhany vagy fürdő).

Azonnal húzzuk le a szennyezett ruházatot és távolítsuk el azt biztonságos módon.

Bőrrel való érintkezés esetén azonnal mossuk le a bőrfelületet szappannal és bő vízzel.

Szemmel való érintkezés esetén:

Szemmel való érintkezés esetén bő vízzel öblítsük a szemet elegendő ideig, miközben a szemhéjat nyitva tartjuk, majd azonnal fordulunk szemészhez!

Védjük a sérült szemet.

Lenyelés esetén:

Egyáltalán nem szabad hánytatni. AZONNAL ORVOSHOZ KELL FORDULNI!

Belélegzés esetén:

A sérültet vigyük friss levegőre és tartsuk melegen, pihenő helyzetben.

4.2. A legfontosabb – akut és késleltetett – tünetek és hatások

Semmi

4.3. A szükséges azonnali orvosi ellátás és különleges ellátás jelzése

Baleset vagy rosszullét esetén azonnal fordulunk orvoshoz (ha lehetséges, mutassuk meg a biztonsági adatlapot vagy a használati útmutatót).

Kezelés:

Semmi

5. SZAKASZ: Tűzvédelmi intézkedések



Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY

5.1. Oltóanyag

Oltóanyag nem ajánlott:

- 5.2. Az anyagból vagy a keverékből származó különleges veszélyek
Ne lélegezzük be a robbanás vagy égés során kialakuló gázokat.
Az égés nehéz füstöt termel.
- 5.3. Tuzoltóknak szóló javaslat
Megfelelő légzőkészüléket használjon!
Külön gyűjtse össze az oltáshoz használt vizet. Ezt a vizet nem szabad a csatornákba önteni!
A nem károsodott tartályokat helyezze a közvetlen veszély zónáján kívülre, ha ez a művelet biztonságosan kivitelezhető.

6. SZAKASZ: Intézkedések véletlenszerű expozícióval

- 6.1. Személyi óvintézkedések, egyéni védőeszközök és vészhelyzeti eljárások
Használjon egyéni védőfelszerelést.
Távolítsa el minden gyulladási forrást.
A helyszínen tartózkodókat vezesse biztonságos helyre.
Nézze át a 7. és 8. pontokban található védelmi intézkedéseket.
- 6.2. Környezetvédelmi óvintézkedések
Akadályozza meg, hogy az anyag a földre/föld alá jusson. Akadályozza meg, hogy az anyag vízbe vagy csatornákba jusson.
Gyűjtse össze a mosáshoz használt szennyezett vizet és ürítse ki.
Ha gáz szabadul fel, vagy gáz jut a vízvezetékekbe, földbe vagy csatornákba, értesítse a felelős hatóságokat.
A gyűjtéshez megfelelő anyagok: szívóhatású anyag, szerves, homok
- 6.3. A területi elhatárolás és a szennyezésmentesítés módszerei és anyagai
Bő vízzel mossa meg.
- 6.4. Hivatkozás más szakaszokra
Lásd a 8. és 13. pontokat is

7. SZAKASZ: Kezelés és tárolás

- 7.1. A biztonságos kezelésre irányuló óvintézkedések
Kerülje a bőrrel és szemmel való érintkezést, a gózok, keverékek belélegzését.
Ne használjon olyan üres tartályt, melynek tisztítása még nem történt meg.
Átontás előtt győződjön meg arról, hogy a tartályokban nincsen maradék összeférhetetlen anyag.
A javasolt védőfelszereléshez nézze át a 8. pontot.

Étkezőhelyiségekbe való belépés előtt le kell venni a szennyezett ruházatot.
Munka közben tilos az étkezés és az ivás!
- 7.2. A biztonságos tárolás feltételei, az esetleges összeférhetetlenséggel együtt
50 °C alatt kell tárolni. Nyílt lángtól és hőforrástól távol kell tartani. Kerülni kell, hogy közvetlen nap érje.
Nyílt lángtól, szikrától és hőforrástól távol kell tartani. Kerülni kell, hogy közvetlen nap érje.
Tartsa távol ételtől, italtól és állateledeltől.
Különösebben egyik sem.
A helyiségekre vonatkozó utasítások:
Hűvös és megfelelően szellőzöttet.
- 7.3. Meghatározott végfelhasználás (végfelhasználások)
Nincs sajátos felhasználási mód

8. SZAKASZ: Az expozíció ellenőrzése/egyéni védelem

- 8.1. Ellenőrzési paraméterek
Szénhidrogének, C3-4; Ásványolaj gáz - CAS: 68476-40-4
MAK - TWA: 2400 mg/m³, 1000 ppm

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



TLV TWA - 1900 mg/m³, 800 ppm

Hydrocarbons, C₇, n-alkanes, isoalkanes, cyclics

EU

propán-2-ol; izopropil-alkohol; izopropanol - CAS: 67-63-0

20101.11 - TWA: 983 mg/m³, 400 ppm

20101.12 - TWA: 492 mg/m³, 200 ppm

ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Megjegyzések: A4, BEI - Eye and URT irr, CNS impair

DYPHENYL OXYDE - CAS: 101-84-8

EU - TWA(8h): 7 mg/m³, 1 ppm - STEL: 14 mg/m³, 2 ppm

ACGIH - TWA(8h): 1 ppm - STEL: 2 ppm - Megjegyzések: (V) - URT and eye irr, nausea

Toluene - CAS: 108-88-3

EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Megjegyzések: Skin

ACGIH - TWA(8h): 20 ppm - Megjegyzések: OTO; A4; BEI - CNS, visual & hearing impair; female repro system eff; pregnancy loss

p-krezol - CAS: 106-44-5

EU - TWA(8h): 22 mg/m³, 5 ppm

ACGIH - TWA(8h): 20 mg/m³ - Megjegyzések: (IFV), Skin, A4 - URT irr

DNEL expozíciós határértékek

Hydrocarbons, C₇, n-alkanes, isoalkanes, cyclics

Szakmunkás: 300 mg/kg - Exponíció: Humán dermatológiai - Frekvencia: Hosszú távú, rendszeres hatások

Szakmunkás: 508 ppm - Exponíció: Humán belélegzés - Frekvencia: Rövid távú, rendszeres hatások

Felhasználó: 149 mg/kg - Exponíció: Humán dermatológiai - Frekvencia: Hosszú távú, rendszeres hatások

Felhasználó: 109 ppm - Exponíció: Humán belélegzés - Frekvencia: Hosszú távú, rendszeres hatások

Felhasználó: 149 mg/kg - Exponíció: Humán orális - Frekvencia: Hosszú távú, rendszeres hatások

propán-2-ol; izopropil-alkohol; izopropanol - CAS: 67-63-0

Szakmunkás: 888 mg/kg - Felhasználó: 319 mg/kg - Exponíció: Humán dermatológiai - Frekvencia: Hosszú távú (ismétlődő)

Szakmunkás: 500 mg/m³ - Felhasználó: 89 mg/m³ - Exponíció: Humán belélegzés - Frekvencia: Hosszú távú (ismétlődő)

Felhasználó: 26 mg/kg - Exponíció: Humán orális - Frekvencia: Hosszú távú (ismétlődő)

DYPHENYL OXYDE - CAS: 101-84-8

Ipari munkás: 59 mg/m³ - Exponíció: Humán belélegzés - Frekvencia: Hosszú távú, rendszeres hatások

Ipari munkás: 58.3 mg/kg - Exponíció: Humán dermatológiai - Frekvencia: Hosszú távú, rendszeres hatások

Ipari munkás: 9.68 mg/m³ - Exponíció: Humán belélegzés - Frekvencia: Hosszú távú, helyi hatások

Ipari munkás: 14 mg/m³ - Exponíció: Humán belélegzés - Frekvencia: Rövid távú, helyi hatások

PNEC expozíciós határértékek

propán-2-ol; izopropil-alkohol; izopropanol - CAS: 67-63-0

Cél: Édesvíz - Érték: 140.9 mg/l

Cél: Édesvíz - Érték: 140.9 mg/l

Cél: Édesvízi üledék - Érték: 552 mg/l

Cél: Talaj (mezőgazdasági) - Érték: 28 mg/kg

Cél: Mikroorganizmusok a szennyvíztisztításban - Érték: 2251 mg/l

DYPHENYL OXYDE - CAS: 101-84-8

Cél: Édesvíz - Érték: 0.0017 mg/l

Cél: Tengervíz - Érték: 0.00017 mg/l

Cél: Édesvízi üledék - Érték: 0.345 mg/kg

Cél: Tengervízi üledék - Érték: 0.0345 mg/kg

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



Cél: Talaj (mezőgazdasági) - Érték: 0.0681 mg/kg

8.2. Az expozíció ellenőrzése

A szem védelme:

Használjon jól illeszkedő védőszemüveget, ne használjon szemlencséket.

A bőr védelme:

Normál használat esetén nincs szükség speciális óvintézkedések alkalmazására.

A kéz védelme:

Használjon teljes védelmet garantáló, pl. PVC, neoprén vagy gumi anyagból készült kesztyűt.

Légzési óvintézkedések:

Használjon olyan megfelelő légzésvédő eszközt.

Termikus veszélyek:

Semmi

Környezeti kitettségi ellenőrzés:

Semmi

Megfelelő műszaki ellenőrzés:

Semmi

9. SZAKASZ: Fizikai és kémiai tulajdonságok

9.1. Az alapvető fizikai és kémiai tulajdonságokra vonatkozó információk

Tulajdonságok	Érték	Mód:	Megjegyzések
Halmazállapot:	Folyadék	--	--
Szín:	színtelen	--	--
Szag:	N.A.	--	--
Olvadáspont/fagyáspont:	N.A.	--	--
Forráspont vagy kezdő forráspont és forráspontartomány:	N.A.	--	--
Tűzveszélyesség:	N.A.	--	--
Felső és alsó robbanási határértékek:	N.A.	--	--
Gyulladáspont:	N.A.	--	--
Öngyulladási hőmérséklet:	N.A.	--	--
Bomlási hőmérséklet:	N.A.	--	--
pH:	N.A.	--	--
Kinematikus viszkozitás:	N.A.	--	--
Vízben oldhatóság:	N.A.	--	--
Oldhatóság olajban:	N.A.	--	--
N-oktanol/víz megoszlási hánnyados (log érték):	N.A.	--	--
Gőznyomás:	N.A.	--	--
Sűrűség és/vagy relatív	N.A.	--	--



Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY

sűrűség:			
Relatív gózsűrűség:	N.A.	--	--
Részecskejellemzők:			
Részecskeméretet:	N.A.	--	--

9.2. Egyéb információk

Nincs más lényeges információ

10. SZAKASZ: Stabilitás és reakciókészség

10.1. Reakciókészség

Normál körülmények között stabil

10.2. Kémiai stabilitás

Normál körülmények között stabil

10.3. A veszélyes reakciók lehetősége

Semmi

10.4. Kerülendő körülmények

Normál körülmények között stabil.

10.5. Nem összeférhető anyagok

Kerülni kell az oxidáló anyagokkal való érintkezést. A termék meggyulladhat.

10.6. Veszélyes bomlástermékek

Semmi.

11. SZAKASZ: Toxikológiai információk

11.1. Az 1272/2008/EK rendeletben meghatározott, veszélyességi osztályokra vonatkozó információk
A termékkel kapcsolatos toxikológiai információk:

COCKPIT CLEANER High Gloss Scented Ocean SPRAY ML 600

a) akut toxicitás

Nincs besorolva

A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

b) bőrkorrózió/bőrirritáció

A termék osztályozása: Skin Irrit. 2 H315

c) súlyos szemkárosodás/szemirritáció

A termék osztályozása: Eye Irrit. 2 H319

d) légzőszervi vagy bőrszenzibilizáció

Nincs besorolva

A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

e) csírasejt-mutagenitás

Nincs besorolva

A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

f) rákkeltő hatás

Nincs besorolva

A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

g) reprodukciós toxicitás

Nincs besorolva

A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

h) egyetlen expozíció utáni célszervi toxicitás (STOT)

A termék osztályozása: STOT SE 3 H336

i) ismétlődő expozíció utáni célszervi toxicitás (STOT)

Nincs besorolva

A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

j) aspirációs veszély

Nincs besorolva



Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY

A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

A termékben talált legfontosabb anyagokkal kapcsolatos toxikológiai információk:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

a) akut toxicitás:

Teszt: LC50 - Kijutás: Inhaláció - Módosulatok: Patkány > 23.3 mg/l - Időtartam: 4h

Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány > 8 ml/kg

Teszt: LD50 - Kijutás: Bőr - Módosulatok: Nyúl 2800-3100 mg/kg
propán-2-ol; izopropil-alkohol; izopropanol - CAS: 67-63-0

a) akut toxicitás:

Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány > 5000 mg/kg

Teszt: LD50 - Kijutás: Bőr - Módosulatok: Nyúl > 5000 mg/kg

Teszt: LC50 - Kijutás: Inhaláció - Módosulatok: Patkány > 10000 ppm - Időtartam: 6h

DYPHENYL OXYDE - CAS: 101-84-8

a) akut toxicitás:

Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány 2830 mg/kg

Teszt: LD50 - Kijutás: Bőr - Módosulatok: Nyúl > 7940 mg/kg

Toluene - CAS: 108-88-3

a) akut toxicitás:

Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány > 5000

Teszt: LD50 - Kijutás: Bőr - Módosulatok: Nyúl > 5000

Teszt: LD50 - Kijutás: Inhaláció - Módosulatok: Patkány > 20 - Időtartam: 4h

p-krezol - CAS: 106-44-5

a) akut toxicitás:

Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány 207 mg/kg

Teszt: LC50 - Kijutás: Inhaláció - Módosulatok: Patkány > 710 mg/m³ - Időtartam: 1h

Teszt: LD50 - Kijutás: Bőr - Módosulatok: Nyúl 301 mg/kg

11.2. Egyéb veszélyekkel kapcsolatos információ

Endokrin károsító tulajdonságok:

Nincsenek jelen endokrin károsító anyagok 0,1%-nál nagyobb koncentrációban.

12. SZAKASZ: Ökológiai információ

12.1. Toxicitás

A megfelelő gyakorlati tapasztalatok alapján kell alkalmazni és el kell kerülni, hogy a termék a környezetet szennyezze.

Szénhidrogének, C3-4; Ásványolaj gáz - CAS: 68476-40-4

a) Akut vízi toxicitás:

Végpont: LC50 - Módosulatok: Daphnia = 14.22 mg/l - Időtartam h: 48

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

b) Krónikus vízi toxicitás:

Végpont: EC50 - Módosulatok: Alga > 10-30 mg/l - Időtartam h: 72

Végpont: LC50 - Módosulatok: Hal > 13.4 mg/l - Időtartam h: 96

propán-2-ol; izopropil-alkohol; izopropanol - CAS: 67-63-0

a) Akut vízi toxicitás:

Végpont: LC50 - Módosulatok: Hal 4200 mg/l - Időtartam h: 96

Végpont: LC50 - Módosulatok: Hal > 100 mg/l - Időtartam h: 48

Végpont: EC50 - Módosulatok: Daphnia > 100 mg/l - Időtartam h: 48

Végpont: EC50 - Módosulatok: Alga > 100 mg/l - Időtartam h: 72

DYPHENYL OXYDE - CAS: 101-84-8

a) Akut vízi toxicitás:

Végpont: LC50 - Módosulatok: Hal 4.2 mg/l - Időtartam h: 96

Végpont: EC50 - Módosulatok: Daphnia 1.7 mg/l - Időtartam h: 48

Végpont: EC50 - Módosulatok: Alga 0.455 mg/l - Időtartam h: 72

Végpont: NOEC - Módosulatok: Alga 0.24 mg/l - Időtartam h: 72

p-krezol - CAS: 106-44-5

b) Krónikus vízi toxicitás:

Végpont: LC50 - Módosulatok: Hal > 16 mg/l - Időtartam h: 24



Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY

Végpont: LC50 - Módosulatok: Daphnia 1.4 mg/l - Időtartam h: 48

12.2. Perzisztencia és lebonthatóság

Semmi

propán-2-ol; izopropil-alkohol; izopropanol - CAS: 67-63-0

Biodegradáció: Gyorsan lebomló - Időtartam h: .10gg - %: 70

12.3. Bioakkumulációs képesség

Toluene - CAS: 108-88-3

Bioakkumuláció: Bioakkumulatív - Teszt: BCF - Biokoncentrációs tényező 90

12.4. A talajban való mobilitás

N.A.

12.5. A PBT- és a vPvB-értékelés eredményei

vPvB anyagok: Semmi - PBT anyagok: Semmi

12.6. Endokrin károsító tulajdonságok

Nincsenek jelen endokrin károsító anyagok 0,1%-nál nagyobb koncentrációban.

12.7. Egyéb káros hatások

Semmi

13. SZAKASZ: Ártalmatlanítási szempontok

13.1. Hulladékkezelési módszerek

Amennyiben lehetséges vissza kell nyerni. Hivatalos hulladékfeldolgozó berendezéssel felszerelt gyűjtőbe v. ellenőrzött porlasztóba kell eljuttatni. Az érvényben levő helyi és országos rendelkezések értelmében kell eljárni.

14. SZAKASZ: Szállításra vonatkozó információk



14.1. UN-szám vagy azonosító szám

ADR-UN Number: 1950

IATA-UN Number: 1950

IMDG-UN Number: 1950

14.2. Az ENSZ szerinti megfelelő szállítási megnevezés

ADR-Shipping Name: AEROSZOLOK, gyúlékony

IATA-Shipping Name: AEROSZOLOK, gyúlékony

IMDG-Shipping Name: AEROSZOLOK, gyúlékony

14.3. Szállítási veszélyességi osztály(ok)

ADR-Class: 2

ADR - Veszély azonosító szám: -

IATA-Class: 2

IATA-Label: 2.1

IMDG-Class: 2

14.4. Csomagolási csoport

ADR-Packing Group: -

IATA-Packing group: -

IMDG-Packing group: -

14.5. Környezeti veszélyek

ADR-környezetszennyező: Nem.

IMDG-Marine pollutant: No

IMDG-EmS: F-D,

S-U

14.6. A felhasználót érintő különleges óvintézkedések

ADR-Subsidiary hazards: See SP63

ADR-S.P.: 190 327 344 625

ADR-Szállítási kategória (Alagútkorlátozási kód): 2 (D)



Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY

IATA-Passenger Aircraft:	203
IATA-Subsidiary hazards:	See SP63
IATA-Cargo Aircraft:	203
IATA-S.P.:	A145 A167 A802
IATA-ERG:	10L
IMDG-Subsidiary hazards:	See SP63
IMDG-Stowage and handling:	SW1 SW22
IMDG-Segregation:	SG69

14.7. Az IMO-szabályok szerinti tengeri ömlesztett szállítás
N.A.
Limited Quantity: 1 L
Exempted Quantity: E0

15. SZAKASZ: Szabályozással kapcsolatos információk

15.1. Az adott anyaggal vagy keverékkel kapcsolatos biztonsági, egészségügyi és környezetvédelmi előírások/jogszabályok

98/24/EK irányelv (A munkájuk során vegyi anyagokkal kapcsolatos kockázatoknak kitett munkavállalók egészségének és biztonságának védelme)

2000/39/EK irányelv (Munkahelyi expozíciós határértékek)

1907/2006/EK (REACH) szabályozás

1272/2008/EK (CLP) szabályozás

790/2009/EK (ATP 1 CLP) szabályozás és 758/2013/EU

2020/878/EU szabályozás

286/2011/EU (ATP 2 CLP) szabályozás

618/2012/EU (ATP 3 CLP) szabályozás

487/2013/EU (ATP 4 CLP) szabályozás

944/2013/EU (ATP 5 CLP) szabályozás

605/2014/EU (ATP 6 CLP) szabályozás

2015/1221/EU (ATP 7 CLP) szabályozás

2016/918/EU (ATP 8 CLP) szabályozás

2016/1179/EU (ATP 9 CLP) szabályozás

2017/776/EU (ATP 10 CLP) szabályozás

2018/669/EU (ATP 11 CLP) szabályozás

2018/1480/EU (ATP 13 CLP) szabályozás

2019/521 /EU (ATP 12 CLP) szabályozás

2020/217/EU (ATP 14 CLP) szabályozás

2020/1182/EU (ATP 15 CLP) szabályozás

2021/643/EU (ATP 16 CLP) szabályozás

2021/849/EU (ATP 17 CLP) szabályozás

2022/692/EU (ATP 18 CLP) szabályozás

Korlátozások a tartalmazott termékkel vagy anyaggal kapcsolatban, a többször módosított 1907/2006 (EC) (REACH) rendelet XVII. mellékletének megfelelően:

A termékkel kapcsolatos megkötések:

Korlátozás 3

Korlátozás 40

A termékben található anyagokkal kapcsolatos megkötések:

Korlátozás 48

Korlátozás 75

Illékony Szerves Vegyületek - VOC = 94.04 %

Illékony Szerves Vegyületek - VOC = 940.41 g/Kg

Illékony Szerves Vegyületek - VOC = 571.77 g/l

Ahol alkalmazható, a következő szabályzat az irányadó:

Tanács 2012/18/EU irányelv (Seveso III)

Az Európai Parlament és a Tanács 648/2004/EK rendelete (a mosó- és tisztítószerekről).

2004/42/EK irányelv (illékony szerves vegyületek)

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



A termék kategóriába tartozik: P3a

15.2. Kémiai biztonsági értékelés

Kémiai biztonsági értékelést nem végeztek a keverékre.

A következő anyagoknál történt meg a kémiai biztonsági értékelés:
Semmi

16. SZAKASZ: Egyéb információk

A 3. bekezdésben használható szöveg:

H220 Rendkívül tűzveszélyes gáz.

H280 Nyomás alatt lévő gázt tartalmaz; hő hatására robbanhat.

H225 Fokozottan tűzveszélyes folyadék és gőz.

H304 Lenyelve és a légitakba kerülve halálos lehet.

H315 Bőrirritáló hatású.

H336 Álmosságot vagy szédülést okozhat.

H411 Mérgező a vízi élővilágra, hosszan tartó károsodást okoz.

EUH066 Ismétlődő expozíció a bőr kiszáradását vagy megrepedezését okozhatja.

H319 Súlyos szemirritációt okoz.

H400 Nagyon mérgező a vízi élővilágra.

H412 Ártalmas a vízi élővilágra, hosszan tartó károsodást okoz.

H361 Feltehetően károsítja a termékenységet vagy a születendő gyermeket.

H373 Ismétlődő vagy hosszabb expozíció esetén károsíthatja a szerveket.

H311 Bőrrel érintkezve mérgező.

H301 Lenyelve mérgező.

H314 Súlyos égési sérülést és szemkárosodást okoz.

Veszélyességi osztály és veszélyességi kategória	Kód	Leírás
Flam. Gas 1A	2.2/1A	Tűzveszélyes gáz, kategória 1A
Aerosols 1	2.3/1	Aeroszolok, kategória 1
Press Gas (Liq.)	2.5/L	Nyomás alatt lévő gázok (Cseppfolyósított gáz)
Flam. Liq. 2	2.6/2	Tűzveszélyes folyadékok, kategória 2
Acute Tox. 3	3.1/3/Dermal	Akut toxicitás (bőrön át), kategória 3
Acute Tox. 3	3.1/3/Oral	Akut toxicitás (szájon át), kategória 3
Asp. Tox. 1	3.10/1	Aspirációs veszély, Kategória 1
Skin Corr. 1B	3.2/1B	Bőrmárás, kategória 1B
Skin Irrit. 2	3.2/2	Bőrirritáció, kategória 2
Eye Irrit. 2	3.3/2	Szemirritáció, kategória 2
Repr. 2	3.7/2	Reprodukciós toxicitás, Kategória 2
STOT SE 3	3.8/3	Célszervi toxicitás – egyszeri expozíció, Kategória 3

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



STOT RE 2	3.9/2	Célszervi toxicitás – ismétlődő expozíció, Kategória 2
Aquatic Acute 1	4.1/A1	Akut vízi toxicitási veszély, Kategória 1
Aquatic Chronic 2	4.1/C2	Krónikus (hosszú távú) vízi toxicitási veszély, Kategória 2
Aquatic Chronic 3	4.1/C3	Krónikus (hosszú távú) vízi toxicitási veszély, Kategória 3

Az előző kiadás módosított bekezdései:

1. SZAKASZ: Az anyag/keverék és a vállalat/vállalkozás azonosítása
2. SZAKASZ: A veszély azonosítása
3. SZAKASZ: Összetétel/összetevőkre vonatkozó információk
8. SZAKASZ: Az expozíció ellenőrzése/egyéni védelem
9. SZAKASZ: Fizikai és kémiai tulajdonságok
11. SZAKASZ: Toxikológiai információk
12. SZAKASZ: Ökológiai információk
14. SZAKASZ: Szállításra vonatkozó információk
15. SZAKASZ: Szabályozással kapcsolatos információk
16. SZAKASZ: Egyéb információk

A keverékek tekintetében az 1272/2008/EK rendelet [CLP] szerinti osztályozás és az osztályozás származtatására alkalmazott eljárás:

Az 1272/2008/EK rendelet szerinti osztályozás	Osztályozási eljárás
Aerosols 1, H222, H229	Vizsgálati adatok alapján
Eye Irrit. 2, H319	Számítási módszer
Skin Irrit. 2, H315	Számítási módszer
STOT SE 3, H336	Számítási módszer
Aquatic Chronic 3, H412	Számítási módszer

Ezt a dokumentumot olyan szakember készítette, aki ezzel kapcsolatban megfelelő képzést kapott
Főbb bibliográfiai források:

ECDIN – Vegyi anyagok környezetvédelmi adat- és információs hálózata – Közös Kutatóközpont, az Európai Közösségek Bizottsága

SAX: AZ IPARI ANYAGOK VESZÉLYES TULAJDONSÁGAI – Nyolcadik kiadás – Van Nostrand Reinold

A közzétett információk a fent jelzett időpontban rendelkezésünkre álló ismeretekre alapulnak.

Kizárolag a megjelölt termékre vonatkoznak és nem képeznek különösebb minőségi garanciát.

A felhasználónak kötelessége megbizonyosodni ezen információk helyessége és teljessége felől, az egyéni felhasználásnak megfelelően.

Ez az adatlap minden előzetes adatlapot érvénytelenít és helyettesít.

ADR: Veszélyes Áruk Nemzetközi Közúti Szállításáról szóló Európai Megállapodás.

ATE: Becsült akut toxicitási érték

ATEmix: Akut toxicitási érték (Keverékek)

CAS: Kémiai Nyilvántartó Szolgálat (az Amerikai Kémiai Társaság részlege).

Biztonsági adatlap.

COCKPIT CLEANER High Gloss Scented Ocean SPRAY



CLP:	Osztályozás, Címkézés, Csomagolás.
DNEL:	Származtatott hatásmentes szint.
EINECS:	Létező Kereskedelmi Vegyi Anyagok Európai Jegyzéke.
GefStoffVO:	Veszélyes Anyagok Német Szabályzata.
GHS:	Vegyi Anyagok Osztályozásának és Címkézésének Egyetemes Harmonizált Rendszere.
IATA:	Nemzetközi Légiszállítási Szövetség.
IATA-DGR:	Nemzetközi Légiszállítási Szövetség - Veszélyes Anyagok Előírásai.
ICAO:	Nemzetközi Polgári Repülési Szervezet.
ICAO-TI:	Nemzetközi Polgári Repülési Szervezet Műszaki Utasítása.
IMDG:	Veszélyes Áruk Nemzetközi Tengerészeti Kódexe.
INCI:	A Kozmetikai Összetevők Nemzetközi Nevezéktana.
KSt:	Robbanási együttható.
LC50:	Közepes halálos koncentráció
LD50:	Közepes halálos dózis
NA:	Nem alkalmazható
PNEC:	Becsült Hatásmentes Koncentráció
RID:	Veszélyes Áruk Nemzetközi Vasúti Fuvarozásáról szóló Szabályzat
STEL:	Rövid Távú Expozíciós Érték
STOT:	Célszervi Toxicitás.
TLV:	Kúszöbérték.
TWA:	Időarányosan súlyozott átlag
WGK:	Vízveszélyeztetési osztály.

Exposure Scenario, 17/07/2019

Substance identity	
Chemical name	IDROCARBURI C3-C4, Miscela (propano,butano,isobutano< 0,1% 1,3-Butadiene)
CAS No.	68476-40-4
EINECS No.	270-681-9

Table of contents

1. ES 1 Use at industrial site

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use as a propellant
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Propellant	PROC1 - PROC2 - PROC3 - PROC8b - PROC9 - PROC12
----------------	---

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

1.2. CS2: Worker Contributing Scenario: Propellant (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - Use of blowing agents in manufacture of foam (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

> 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Keep drains in watertight containers while awaiting dismantling or subsequent recycling
- Use in contained systems
- Ensure operatives are trained to minimise exposures.
- Ensure that direct skin contact is avoided.
- Clear transfer lines prior to de-coupling.
- Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
- Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 17/07/2019

Substance identity

Chemical name	Heptane HYDROCARBONS C7, N-ALKANES, ISOALKANES, CYCLICS
EINECS No.	927-510-4

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Use at industrial site
4. **ES 4** Widespread use by professional workers

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC9 - PROC10 - PROC13 - PROC14 - PROC15
----------------	---

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 400 t(tonnes)/year
Daily amount per site 20000 kg/day

Maximum allowable site tonnage (MSafe): 62000 kg/day

Release type: Continuous release

Emission days: 20 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 90 %
No discharge of substance into waste water	Water - minimum efficiency of: 88.2 %

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Product residual disposal complies with applicable regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

1.2. CS2: Worker Contributing Scenario: Industrial (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15)

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - Roller application or brushing - Treatment of articles by dipping and pouring - Tabletting, compression, extrusion, pelletisation, granulation - Use as laboratory reagent (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Remove spills immediately

Ensure operatives are trained to minimise exposures.

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear suitable face shield.

Use suitable eye protection.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario: Covered by (ERC4)

Release route	Release rate	Release estimation method
Air	98 %	N/A
Water	0.07 %	N/A
soil	0 %	N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers	
2.1 TITLE SECTION	
Exposure Scenario name	Use in coatings
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Environment Contributing Scenario	
CS1 Covered by	ERC8a - ERC8d
Worker Contributing Scenario	
CS2 General use from professional operators	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15 - PROC19
2.2 Conditions of use affecting exposure	
2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
<i>Amount used, frequency and duration of use (or from service life)</i>	
Amounts used: Annual site tonnage 0.15 t(onnes)/year Daily amount per site 0.41 kg/day	
Maximum allowable site tonnage (MSafe): 1500 kg/day	
Release type: Continuous release	
Emission days: 365 days per year	
<i>Technical and organisational conditions and measures</i>	
Control measures to prevent releases Treat air emission to provide the required removal efficiency of (%): Prevent discharge of undissolved substance to or recover from onsite wastewater.	
<i>Conditions and measures related to sewage treatment plant</i>	
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 96.2 %	
STP effluent (m³/day): 2000	
<i>Conditions and measures related to treatment of waste (including article waste)</i>	
Waste treatment Do not apply industrial sludge to natural soils. Product residual disposal complies with applicable regulations.	
<i>Other conditions affecting environmental exposure</i>	
Local marine water dilution factor: 100	
Local freshwater dilution factor: 10	
<i>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.</i>	

Additional Good Practice Advice:

Do not use sludge as fertiliser.

2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent - Manual activities involving hand contact (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)
---------------------------	---

Product (article) characteristics
Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure
Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures
Technical and organisational measures

Use in contained systems

Ensure operatives are trained to minimise exposures.

Carry out in a vented booth or extracted enclosure.

Conditions and measures related to personal protection, hygiene and health evaluation
Personal protection

Wear suitable gloves tested to EN374.

Wear suitable face shield.

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

2.3 Exposure estimation and reference to its source
2.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Release route	Release rate	Release estimation method
Air	98 %	N/A
soil	1 %	N/A
Water	0.1 %	N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by

the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Use at industrial site	
3.1 TITLE SECTION	
Exposure Scenario name	Use in cleaning agents
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)
Environment Contributing Scenario	
CS1 Covered by	ERC4
Worker Contributing Scenario	
CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
3.2 Conditions of use affecting exposure	
3.2. CS1: Environment Contributing Scenario: Covered by (ERC4)	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
<i>Amount used, frequency and duration of use (or from service life)</i>	
Amounts used: Annual site tonnage 74 t(tonnes)/year Daily amount per site 3700 kg/day	
Maximum allowable site tonnage (MSafe): 4600000 kg/day	
Release type: Continuous release	
Emission days: 20 days per year	
Technical and organisational conditions and measures	
Control measures to prevent releases	
Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 70 %
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Conditions and measures related to sewage treatment plant	
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 96.2 %	
STP effluent (m³/day): 2000	
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment Do not apply industrial sludge to natural soils. External treatment and disposal of waste should comply with applicable local and/or national regulations.	
Other conditions affecting environmental exposure	

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Do not apply industrial sludge to natural soils.

3.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Remove spills immediately

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

3.3 Exposure estimation and reference to its source

3.3. CS1: Environment Contributing Scenario: Covered by (ERC4)

Release route	Release rate	Release estimation method
Air	1 %	N/A
Water	3E-06 %	N/A
soil	0 %	N/A

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by

the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Widespread use by professional workers	
4.1 TITLE SECTION	
Exposure Scenario name	Cleaning agent
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Environment Contributing Scenario	
CS1 Covered by	ERC8a - ERC8d
Worker Contributing Scenario	
CS2 General use from professional operators	PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13
4.2 Conditions of use affecting exposure	
4.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
<i>Amount used, frequency and duration of use (or from service life)</i>	
Amounts used: Annual site tonnage 0.012 t(onnes)/year Daily amount per site 0.032 kg/day	
Maximum allowable site tonnage (MSafe): 170 kg/day	
Release type: Continuous release	
Emission days: 365 days per year	
<i>Technical and organisational conditions and measures</i>	
Control measures to prevent releases Treat air emission to provide the required removal efficiency of (%): Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils.	
<i>Conditions and measures related to sewage treatment plant</i>	
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 96.2 %	
STP effluent (m³/day): 2000	
<i>Conditions and measures related to treatment of waste (including article waste)</i>	
Waste treatment Do not apply industrial sludge to natural soils. External treatment and disposal of waste should comply with applicable local and/or national regulations.	
<i>Other conditions affecting environmental exposure</i>	
Local marine water dilution factor: 100	
Local freshwater dilution factor: 10	

4.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Remove spills immediately

Ensure operatives are trained to minimise exposures.

Handle substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Ventilation rate: Provide forced ventilation

4.3 Exposure estimation and reference to its source

4.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Release route	Release rate	Release estimation method
Air	2 %	N/A
soil	0 %	N/A
Water	1E-06 %	N/A

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 16/07/2019

Substance identity	
Chemical name	ALCOOL ISOPROPILICO; PROPAN-2-OLO
CAS No.	67-63-0
EINECS No.	200-661-7

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Use at industrial site
3. **ES 3** Widespread use by professional workers
4. **ES 4** Widespread use by professional workers
5. **ES 5** Widespread use by professional workers
6. **ES 6** Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)
7. **ES 7** Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)
8. **ES 8** Consumer use; Anti-freeze and de-icing products (PC4)

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Solvent-based process	ERC4
---------------------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
----------------	---

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

1.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Keep drains in watertight containers while awaiting dismantling or subsequent recycling
- Ensure that direct skin contact is avoided.
- Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
- Drain down system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Use at industrial site	
2.1 TITLE SECTION	
Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC4
Worker Contributing Scenario	
CS2 Industrial	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13 - PROC15
2.2 Conditions of use affecting exposure	
2.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
2.2. CS2: Worker Contributing Scenario: Industrial (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)	
Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)
Product (article) characteristics	
Physical form of product:	
Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product:	
Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration:	
Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures	
Keep drains in watertight containers while awaiting dismantling or subsequent recycling Ensure that direct skin contact is avoided. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Carry out in a vented booth or extracted enclosure.	
Conditions and measures related to personal protection, hygiene and health evaluation	

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

2.3 Exposure estimation and reference to its source

N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Widespread use by professional workers	
3.1 TITLE SECTION	
Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC8a - ERC8d
Worker Contributing Scenario	
CS2 General use from professional operators	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15 - PROC19
3.2 Conditions of use affecting exposure	
3.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
3.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)	
Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent - Manual activities involving hand contact (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)
Product (article) characteristics	
Physical form of product:	
Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product:	
Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration:	
Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures	
Ensure that direct skin contact is avoided. Carry out in a vented booth or extracted enclosure. Store substance within a closed system.	
Conditions and measures related to personal protection, hygiene and health evaluation	

Personal protection

Use suitable eye protection.

Wear a respirator conforming to EN140.

3.3 Exposure estimation and reference to its source

N/A

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Widespread use by professional workers	
4.1 TITLE SECTION	
Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC8a - ERC8d
Worker Contributing Scenario	
CS2 General use from professional operators	PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15
4.2 Conditions of use affecting exposure	
4.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
4.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)
Product (article) characteristics	
Physical form of product:	
Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product:	
Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration:	
Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures	
Ensure that direct skin contact is avoided. Avoid carrying out activities involving exposure for more than 15 minutes per day. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Store substance within a closed system.	
Conditions and measures related to personal protection, hygiene and health evaluation	

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

4.3 Exposure estimation and reference to its source

N/A

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

5. ES 5 Widespread use by professional workers	
5.1 TITLE SECTION	
Exposure Scenario name	De-icing and anti-icing applications
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC8d
Worker Contributing Scenario	
CS2 General use from professional operators	PROC1 - PROC2 - PROC8a - PROC8b - PROC11
5.2 Conditions of use affecting exposure	
5.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
5.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC8a, PROC8b, PROC11)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Non industrial spraying (PROC1, PROC2, PROC8a, PROC8b, PROC11)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Ensure that direct skin contact is avoided. Avoid carrying out activities involving exposure for more than 1 hour per day. Clear transfer lines prior to de-coupling.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Use suitable eye protection.	
Other conditions affecting worker exposure	
Temperature: Assumes use at not more than 20 °C above ambient temperature.	
5.3 Exposure estimation and reference to its source	

N/A

5.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

6. ES 6 Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)	
6.1 TITLE SECTION	
Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Non-metal surface treatment products (PC15) - Ink and toners (PC18) - Lubricants, greases, release products (PC24) - Polishes and wax blends (PC31) - Textile dyes and impregnating products (PC34)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC8a - ERC8d
Consumer Contributing Scenario	
CS2 Use in coatings	PC9b - PC9a - PC1 - PC4 - PC8 - PC15 - PC18 - PC24 - PC31 - PC34
6.2 Conditions of use affecting exposure	
6.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
6.2. CS2: Consumer Contributing Scenario: Use in coatings (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)	
Product Categories	Fillers, putties, plasters, modelling clay - Coatings and paints, thinners, paint removers - Adhesives, sealants - Anti-freeze and de-icing products - Biocidal products - Non-metal surface treatment products - Ink and toners - Lubricants, greases, release products - Polishes and wax blends - Textile dyes and impregnating products (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure > 10 kPa at STP	
Concentration of substance in product: Covers concentrations up to 50 %	
Additional conditions human health Covers skin contact area up to 430 cm ²	
Amount used, frequency and duration of use/exposure	
Amounts used: Amount per use 10 g	
Frequency: Covers exposure up to 1 events per day	
Frequency: Covers frequency up to: 365 days per year	

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

6.3 Exposure estimation and reference to its source

N/A

6.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

7. ES 7 Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)	
7.1 TITLE SECTION	
Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Air care products (PC3) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Lubricants, greases, release products (PC24) - Washing and cleaning products (PC35) - Welding and soldering products, flux products (PC38)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC8a - ERC8d
Consumer Contributing Scenario	
CS2 Detergent liquids	PC9a - PC3 - PC4 - PC8 - PC24 - PC35 - PC38
7.2 Conditions of use affecting exposure	
7.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
7.2. CS2: Consumer Contributing Scenario: Detergent liquids (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)	
Product Categories	Coatings and paints, thinners, paint removers - Air care products - Anti-freeze and de-icing products - Biocidal products - Lubricants, greases, release products - Washing and cleaning products - Welding and soldering products, flux products (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)
Product (article) characteristics	
Physical form of product:	Liquid, vapour pressure > 10 kPa at STP
Concentration of substance in product:	Covers concentrations up to 50 %
Amount used, frequency and duration of use/exposure	
Amounts used:	Amount per use 100 g
Frequency:	Covers use up to 365 days per year
Frequency:	Covers use up to 1 uses per day
Other conditions affecting consumers exposure	
Room size:	Covers use in a one car garage (>34 m ³) under typical ventilation.
Temperature:	Covers use at ambient temperatures.
Additional conditions human health	
Covers skin contact area up to 428 cm ²	

7.3 Exposure estimation and reference to its source

N/A

7.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

8. ES 8 Consumer use; Anti-freeze and de-icing products (PC4)

8.1 TITLE SECTION

Exposure Scenario name	De-icing and anti-icing applications
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Anti-freeze and de-icing products (PC4)

Environment Contributing Scenario

CS1 Solvent-based process	ERC4
----------------------------------	------

Consumer Contributing Scenario

CS2 De-icing and anti-icing applications	PC24
---	------

8.2 Conditions of use affecting exposure

8.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
---	--

8.2. CS2: Consumer Contributing Scenario: De-icing and anti-icing applications (PC24)

Product Categories	Lubricants, greases, release products (PC24)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

Concentration of substance in product:

Covers concentrations up to 10 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 2000 g

Duration:

Covers use up to 0.25 h/event

Frequency:

Covers exposure up to 365 days per year

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

Additional conditions human health

Covers skin contact area up to 428 cm²

8.3 Exposure estimation and reference to its source

N/A

8.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.