



-i biztonsági adatlap. 6/6/2022, ellenőrzés 6

1. SZAKASZ: Az anyag/keverék és a vállalat/vállalkozás azonosítása

1.1. Termékazonosító

A készítmény azonosítása:

Kereskedelmi név: WIZZY RINNOVA PELLE

Kereskedelmi kód: 19351

1.2. Az anyag vagy keverék lényeges azonosított felhasználásai, illetve ellenjavallt felhasználásai
Javasolt felhasználási mód:

impregnált bőr felújító kendő

1.3. A biztonsági adatlap szállítójának adatai

Szállító:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

A biztonsági adatlapért felelős illetékes személy:

arexons@arexons.it

1.4. Sürgösségi telefonszám

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Egészségügyi Toxikológiai Tájékoztató Szolgálat' (ETTSz) +36-80-20-11-99 (0-24 órában,
díjmentesen hívható – csak Magyarországról)

2. SZAKASZ: A veszély azonosítása

2.1. Az anyag vagy keverék besorolása

EC 1272/2008 (CLP) irányelv kritériumai:

CE 1272/2008 (CLP) Szabályzat értelmében a termék nem számít veszélyes anyagnak.

Az emberi egészségre és a környezetre káros fizikokémiai hatások:

Egyéb veszélyek nincsenek

2.2. Címkézési elemek

CE 1272/2008 (CLP) Szabályzat értelmében a termék nem számít veszélyes anyagnak.

Veszélyt jelző piktogramok:

Semmi

Figyelmeztető mondatok:

Semmi

Óvintézkedésre vonatkozó mondatok:

Semmi

Különleges utasítások:

EUH208 1,2-benzizotiazol-3(2H)-on; 1,2-benzizotiazolin-3-on-t tartalmaz. Allergiás reakciót válthat ki

EUH208 5-klór-2-metil-2H-izotiazol-3-on és 2-metil-2H-izotiazol-3-on (3:1) keveréke-t tartalmaz. Allergiás reakciót válthat ki

Különleges intézkedések a többször módosított REACH rendelet XVII. mellékletének megfelelően:

Semmi

Az Európai Parlament és a Tanács 648/2004/EK rendelete (a mosó- és tisztítószerekről).

A termék tartalma:

Amfoter felületaktív anyagok, Nem ionos felületaktív anyagok < 5 %

Biztonsági adatlap. WIZZY RINNOVA PELLE



A termék tartalmaz még: Illatanyagok
Tartósítószerke: LAURYLAMINE DIPROPYLENEDIAMINE, Piridin-2-tiol-1-oxid, nátriumsó, 1,2-benzizotiazol-3(2H)-on; 1,2-benzizotiazolin-3-on, 1,2-benzizotiazol-3(2H)-on; 1,2-benzizotiazolin-3-on, 5-klór-2-metil-2H-izotiazol-3-on és 2-metil-2H-izotiazol-3-on (3:1) keveréke

2.3. Egyéb veszélyek
Nincs jelen PBT, vPvB vagy endokrin károsító anyag 0,1%-nál nagyobb koncentrációban.
Egyéb veszélyek:
Egyéb veszélyek nincsenek

3. SZAKASZ: Összetétel vagy az összetevőkre vonatkozó adatok

3.1. Anyagok

N.A.

3.2. Keverékek

A CLP rendelet és a vonatkozó osztályozás értelmében veszélyesnek minősülő összetevők:

>= 1% - < 2% etán-diol; etilén-glikol

REACH No.: 01-2119456816-28, Index szám: 603-027-00-1, CAS: 107-21-1, EC: 203-473-3

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.9/2 STOT RE 2 H373 (vese) (szájon át)

>= 0.5% - < 1% Amines, C12-14(even numbered)-alkyldimethyl, N-oxides

REACH No.: 01-2119490061-47, EC: 931-292-6

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 4.1/A1 Aquatic Acute 1 H400

⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.005% - < 0.01% 1,2-benzizotiazol-3(2H)-on; 1,2-benzizotiazolin-3-on

Index szám: 613-088-00-6, CAS: 2634-33-5, EC: 220-120-9

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1 Skin Sens. 1 H317

⚠ 4.1/A1 Aquatic Acute 1 H400

⚠ 4.1/C2 Aquatic Chronic 2 H411

Egyedi koncentrációs határértékek:

C >= 0,005%: EUH208

C >= 0,05%: Skin Sens. 1 H317

2 ppm 5-klór-2-metil-2H-izotiazol-3-on és 2-metil-2H-izotiazol-3-on (3:1) keveréke

Index szám: 613-167-00-5, CAS: 55965-84-9

⚠ 3.1/2/Inhal Acute Tox. 2 H330

⚠ 3.1/2/Dermal Acute Tox. 2 H310

⚠ 3.1/3/Oral Acute Tox. 3 H301

⚠ 3.2/1C Skin Corr. 1C H314

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1A Skin Sens. 1A H317

⚠ 4.1/A1 Aquatic Acute 1 H400 M=100.

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=100.

EUH071

Egyedi koncentrációs határértékek:

Biztonsági adatlap. WIZZY RINNOVA PELLE



C >= 0,6%: Skin Corr. 1C H314
0,06% <= C < 0.6%: Skin Irrit. 2 H315
C >= 0,6%: Eye Dam. 1 H318
0,06% <= C < 0.6%: Eye Irrit. 2 H319
C >= 0,0015%: Skin Sens. 1A H317

4. SZAKASZ: Elsősegély-nyújtási intézkedések

4.1. Az elsősegély-nyújtási intézkedések ismertetése

Bőrrel való érintkezés esetén:

Bő, szappanos vízzel kell lemosni.

Szemmel való érintkezés esetén:

Ha szembe kerül, bő vízzel azonnal ki kell mosni és orvoshoz kell fordulni.

Lenyelés esetén:

Egyáltalán nem szabad hánytatni. AZONNAL ORVOSHOZ KELL FORDULNI!

Belélegzés esetén:

A sérültet vigyük friss levegőre és tartsuk melegen, pihenő helyzetben.

4.2. A legfontosabb – akut és késleltetett – tünetek és hatások

Semmi

4.3. A szükséges azonnali orvosi ellátás és különleges ellátás jelzése

Kezelés:

Semmi

5. SZAKASZ: Tuzoltási intézkedések

5.1. Oltóanyag

Széndioxid.

Porral.

hab

Vízpermet

Oltóanyag nem ajánlott:

Közvetlen vízszugár használata tilos

5.2. Az anyaghoz vagy a keverékhez társuló különleges veszélyek

Ne lélegezzük be a robbanás vagy égés során kialakuló gázokat.

Az égés nehéz füstöt termel.

5.3. Tuzoltóknak szóló javaslat

Megfelelő légzőkészüléket használjon!

Külön gyűjtse össze az oltáshoz használt vizet. Ezt a vizet nem szabad a csatornába önteni!

A nem károsodott tartályokat helyezze a közvetlen veszély zónáján kívülre, ha ez a művelet biztonságosan kivitelezhető.

6. SZAKASZ: Intézkedések véletlenszerű környezetbe jutás esetén

6.1. Személyi óvintézkedések, egyéni védőeszközök és vészhelyzeti eljárások

Használjon egyéni védőfelszerelést.

A helyszínen tartózkodókat vezesse biztonságos helyre.

Nézze át a 7. és 8. pontokban található védelmi intézkedéseket.

6.2. Környezetvédelmi óvintézkedések

Akadályozza meg, hogy az anyag a földre/föld alá jusson. Akadályozza meg, hogy az anyag vízbe vagy csatornába jusson.

Gyűjtse össze a mosáshoz használt szennyezett vizet és ürítse ki.

Ha gáz szabadul fel, vagy gáz jut a vízvezetékekbe, földbe vagy csatornába, értesítse a felelős



hatóságokat.

A gyűjtéshez megfelelő anyagok: szívóhatású anyag, szerves, homok

6.3. A területi elhatárolás és a szennyezésmentesítés módszerei és anyagai
Bő vízzel mossa meg.

6.4. Hivatkozás más szakaszokra
Lásd a 8. és 13. pontokat is

7. SZAKASZ: Kezelés és tárolás

7.1. A biztonságos kezelésre irányuló óvintézkedések
Kerülje a bőrrel és szemmel való érintkezést, a gőzök, keverékek belélegzését.
A javasolt védőfelszereléshez nézze át a 8. pontot.

Munka közben tilos az étkezés és az ivás!

7.2. A biztonságos tárolás feltételei, az esetleges összeférhetlenséggel együtt
Tartsa távol ételtől, italtól és állateledeltől.

Összeférhetetlen anyagok:

Különösebben egyik sem.

A helyiségekre vonatkozó utasítások:

A jól lezárt tárolóedényeket hűvös és szellős helyen, hőforrástól távol kell tárolni.

7.3. Meghatározott végfelhasználás (végfelhasználások)
Nincs sajátos felhasználási mód

8. SZAKASZ: Az expozíció elleni védekezés/egyéni védelem

8.1. Ellenőrzési paraméterek

etán-diol; etilén-glikol - CAS: 107-21-1

EU - TWA(8h): 52 mg/m³, 20 ppm - STEL: 104 mg/m³, 40 ppm - Megjegyzések: Skin

ACGIH - TWA(8h): 25 ppm - STEL: 50 ppm - Megjegyzések: (V), A4 - URT irr

ACGIH - STEL: 10 mg/m³ - Megjegyzések: (I, H), A4 - URT irr

DNEL expozíciós határértékek

Amines, C12-14(even numbered)-alkyldimethyl, N-oxides

Szaktmunkás: 6.2 mg/m³ - Felhasználó: 1.53 mg/m³ - Expozíció: Humán belélegzés -

Frekvencia: Hosszú távú, rendszeres hatások

Szaktmunkás: 11 mg/kg - Felhasználó: 5.5 mg/kg - Expozíció: Humán dermatológiai -

Frekvencia: Hosszú távú, helyi hatások

Felhasználó: 0.44 mg/kg - Expozíció: Humán orális - Frekvencia: Hosszú távú, rendszeres hatások

PNEC expozíciós határértékek

Amines, C12-14(even numbered)-alkyldimethyl, N-oxides

Cél: Édesvíz - Érték: 0.0335 mg/l

Cél: Tengervíz - Érték: 0.00335 mg/l

Cél: Édesvízi üledék - Érték: 0.0335 mg/kg

Cél: Tengervízi üledék - Érték: 0.0335 mg/kg

Cél: 09 - Érték: 24 mg/l

8.2. Az expozíció elleni védekezés

A szem védelme:

Normális használat esetén nem szükséges. Dolgozzon mindenesetre a megszokott gyakorlat szerint.

A bőr védelme:

Normál használat esetén nincs szükség speciális óvintézkedések alkalmazására.

A kéz védelme:

Normális használat esetén nem szükséges.

Légzési óvintézkedések:

Normál használat esetén nem szükséges.

Termikus veszélyek:

Semmi

Biztonsági adatlap. WIZZY RINNOVA PELLE



Környezeti kitétségi ellenőrzés:

Semmi

Megfelelő műszaki ellenőrzés:

Semmi

9. SZAKASZ: Fizikai és kémiai tulajdonságok

9.1. Az alapvető fizikai és kémiai tulajdonságokra vonatkozó információk

Tulajdonságok	Érték	Mód:	Megjegyzések
Halmazállapot:	Folyadék	--	--
Szín:	bézs	--	--
Szag:	jellegzetes	--	--
Olvadáspont/fagyáspont:	N.A.	--	--
Forráspont vagy kezdő forráspont és forrásponttartomány:	>100°C	--	--
Tűzveszélyesség:	N.A.	--	--
Felső és alsó robbanási határértékek:	N.A.	--	--
Gyulladáspont:	nem gyúlékony	08	--
Öngyulladási hőmérséklet:	N.A.	--	--
Bomlási hőmérséklet:	N.A.	--	--
pH:	6.9	--	--
Kinematikus viszkozitás:	N.A.	--	--
Vízben oldhatóság:	oldódó	--	--
Oldhatóság olajban:	N.A.	--	--
N-oktanol/víz megoszlási hányados (log érték):	N.A.	--	--
Gőznyomás:	N.A.	--	--
Sűrűség és/vagy relatív sűrűség:	1,007 g/cm ³	--	--
Relatív gőzsűrűség:	N.A.	--	--
Részecskejellemzők:			
Részecskeméretet:	N.A.	--	--

9.2. Egyéb információk

Nincs más lényeges információ



10. SZAKASZ: Stabilitás és reakciókészség

- 10.1. Reakciókészség
Normál körülmények között stabil
- 10.2. Kémiai stabilitás
Normál körülmények között stabil
- 10.3. A veszélyes reakciók lehetősége
Semmi
- 10.4. Kerülendő körülmények
Normál körülmények között stabil.
- 10.5. Nem összeférhető anyagok
Különösebben semmi.
- 10.6. Veszélyes bomlástermékek
Semmi.

11. SZAKASZ: Toxikológiai adatok

11.1. Az 1272/2008/EK rendeletben meghatározott, veszélyességi osztályokra vonatkozó információk
A termékkel kapcsolatos toxikológiai információk:

WIZZY RINNOVA PELLE

- a) akut toxicitás
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- b) bőrkorrózió/bőrirritáció
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- c) súlyos szemkárosodás/szemirritáció
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- d) légzőszervi vagy bőrszenzibilizáció
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- e) csírasejt-mutagenitás
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- f) rákkeltő hatás
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- g) reprodukciós toxicitás
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- h) egyetlen expozíció utáni célszervi toxicitás (STOT)
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- i) ismétlődő expozíció utáni célszervi toxicitás (STOT)
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.
- j) aspirációs veszély
Nincs besorolva
A rendelkezésre álló adatok alapján az osztályozás kritériumai nem teljesülnek.

A termékben talált legfontosabb anyagokkal kapcsolatos toxikológiai információk:

Amines, C12-14(even numbered)-alkyldimethyl, N-oxides

a) akut toxicitás:

Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány 1064 mg/kg

g) reprodukciós toxicitás:

Biztonsági adatlap. WIZZY RINNOVA PELLE



- Teszt: NOEL - Kijutás: Szájon át 100 mg/kg - Forrás: OECD 422
Teszt: arx1 - Kijutás: Szájon át 25 mg/kg
i) ismétlődő expozíció utáni célszervi toxicitás (STOT):
Teszt: NOAEL - Kijutás: Szájon át 88 mg/kg
1,2-benzizotiazol-3(2H)-on; 1,2-benzizotiazolin-3-on - CAS: 2634-33-5
a) akut toxicitás:
Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány 1193 mg/kg
Teszt: LD50 - Kijutás: Bőr - Módosulatok: Patkány 4115 mg/kg
b) bőrkorrózió/bőrirritáció:
Teszt: Irritálja a bőrt Pozitív
c) súlyos szemkárosodás/szemirritáció:
Teszt: Marja a szemet Pozitív
d) légzőszervi vagy bőrszenzibilizáció:
Teszt: Bőr szenzitiváció - Kijutás: Bőr Pozitív
5-klór-2-metil-2H-izotiazol-3-on és 2-metil-2H-izotiazol-3-on (3:1) keveréke - CAS: 55965-84-9
a) akut toxicitás:
Teszt: LD50 - Kijutás: Szájon át - Módosulatok: Patkány 100 mg/kg
Teszt: LD50 - Kijutás: Bőr - Módosulatok: Patkány 300 mg/kg

- 11.2. Egyéb veszélyekkel kapcsolatos információ
Endokrin károsító tulajdonságok:
Nincsenek jelen endokrin károsító anyagok 0,1%-nál nagyobb koncentrációban.

12. SZAKASZ: Ökológiai adatok

- 12.1. Toxicitás
A megfelelő gyakorlati tapasztalatok alapján kell alkalmazni és el kell kerülni, hogy a termék a környezetet szennyezze.
Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
a) Akut vízi toxicitás:
Végpont: LC50 - Módosulatok: Hal 2.67 mg/l
Végpont: EC50 - Módosulatok: Daphnia 3.1 mg/l
Végpont: CE6 - Módosulatok: Alga 0.19 mg/l
b) Krónikus vízi toxicitás:
Végpont: NOEC - Módosulatok: Alga 0.067 mg/l
1,2-benzizotiazol-3(2H)-on; 1,2-benzizotiazolin-3-on - CAS: 2634-33-5
a) Akut vízi toxicitás:
Végpont: LC50 - Módosulatok: Hal 2.18 mg/l - Időtartam h: 96
Végpont: EC50 - Módosulatok: Daphnia 2.94 mg/l - Időtartam h: 48
Végpont: CE6 - Módosulatok: Alga 0.11 mg/l - Időtartam h: 72
5-klór-2-metil-2H-izotiazol-3-on és 2-metil-2H-izotiazol-3-on (3:1) keveréke - CAS: 55965-84-9
a) Akut vízi toxicitás:
Végpont: LC50 - Módosulatok: Hal 0.19 mg/l - Időtartam h: 96
Végpont: EC50 - Módosulatok: Daphnia 0.16 mg/l - Időtartam h: 48
Végpont: EC50 - Módosulatok: Alga 0.1 mg/l - Időtartam h: 72
- 12.2. Perzisztencia és lebonthatóság
Semmi
Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
Biodegradáció: Gyorsan lebomló - Időtartam h: 28gg - %: 80
1,2-benzizotiazol-3(2H)-on; 1,2-benzizotiazolin-3-on - CAS: 2634-33-5
Biodegradáció: Gyorsan lebomló - Teszt: BIOGDG06
- 12.3. Bioakkumulációs képesség
Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
Teszt: log Pow 2.7
5-klór-2-metil-2H-izotiazol-3-on és 2-metil-2H-izotiazol-3-on (3:1) keveréke - CAS: 55965-84-9
Teszt: log Pow 0.401
- 12.4. A talajban való mobilitás

Biztonsági adatlap. WIZZY RINNOVA PELLE



- N.A.
- 12.5. A PBT- és a vPvB-értékelés eredményei
vPvB anyagok: Semmi - PBT anyagok: Semmi
- 12.6. Endokrin károsító tulajdonságok
Nincsenek jelen endokrin károsító anyagok 0,1%-nál nagyobb koncentrációban.
- 12.7. Egyéb káros hatások
Semmi

13. SZAKASZ: Ártalmatlanítási szempontok

- 13.1. Hulladékkezelési módszerek
Amennyiben lehetséges, vissza kell nyerni. Az érvényben levő helyi és országos rendelkezések értelmében kell eljárni.

14. SZAKASZ: Szállításra vonatkozó információk

- 14.1. UN-szám vagy azonosító szám
A szállítási szabályok értelmében nem veszélyes áru.
- 14.2. Az ENSZ szerinti megfelelő szállítási megnevezés
N.A.
- 14.3. Szállítási veszélyességi osztály(ok)
N.A.
- 14.4. Csomagolási csoport
N.A.
- 14.5. Környezeti veszélyek
ADR-környezetszennyező: Nem.
IMDG-Marine pollutant: No
- 14.6. A felhasználót érinto különleges óvintézkedések
N.A.
- 14.7. Az IMO-szabályok szerinti tengeri ömlesztett szállítás
N.A.

15. SZAKASZ: Szabályozással kapcsolatos információk

- 15.1. Az adott anyaggal vagy keverékkel kapcsolatos biztonsági, egészségügyi és környezetvédelmi előírások/jogszabályok

98/24/EK irányelv (A munkájuk során vegyi anyagokkal kapcsolatos kockázatoknak kitett munkavállalók egészségének és biztonságának védelme)
2000/39/EK irányelv (Munkahelyi expozíciós határértékek)
1907/2006/EK (REACH) szabályozás
1272/2008/EK (CLP) szabályozás
790/2009/EK (ATP 1 CLP) szabályozás és 758/2013/EU
2020/878/EU szabályozás
286/2011/EU (ATP 2 CLP) szabályozás
618/2012/EU (ATP 3 CLP) szabályozás
487/2013/EU (ATP 4 CLP) szabályozás
944/2013/EU (ATP 5 CLP) szabályozás
605/2014/EU (ATP 6 CLP) szabályozás
2015/1221/EU (ATP 7 CLP) szabályozás
2016/918/EU (ATP 8 CLP) szabályozás
2016/1179/EU (ATP 9 CLP) szabályozás
2017/776/EU (ATP 10 CLP) szabályozás
2018/669/EU (ATP 11 CLP) szabályozás
2018/1480/EU (ATP 13 CLP) szabályozás
2019/521 /EU (ATP 12 CLP) szabályozás

Biztonsági adatlap. WIZZY RINNOVA PELLE



2020/217/EU (ATP 14 CLP) szabályozás
2020/1182/EU (ATP 15 CLP) szabályozás
2021/643/EU (ATP 16 CLP) szabályozás

Korlátozások a tartalmazott termékkel vagy anyaggal kapcsolatban, a többször módosított 1907/2006 (EC) (REACH) rendelet XVII. mellékletének megfelelően:

A termékkel kapcsolatos megkötések:

Nincs korlátozás.

A termékben található anyagokkal kapcsolatos megkötések:

Korlátozás 40

Korlátozás 75

Illékony Szerves Vegyületek - VOC = 1.00 %

Illékony Szerves Vegyületek - VOC = 10.05 g/Kg

Illékony Szerves Vegyületek - VOC = 10.12 g/l

Ahol alkalmazható, a következő szabályzat az irányadó:

Tanács 2012/18/EU irányelve (Seveso III)

Az Európai Parlament és a Tanács 648/2004/EK rendelete (a mosó- és tisztítószerokról).

2004/42/EK irányelv (illékony szerves vegyületek)

NA

15.2. Kémiai biztonsági értékelés

Kémiai biztonsági értékelést nem végeztek a keverékre.

A következő anyagoknál történt meg a kémiai biztonsági értékelés:

Semmi

16. SZAKASZ: Egyéb információk

A 3. bekezdésben használható szöveg:

H302 Lenyelve ártalmas.

H373 (vese) (szájon át) Lehet, hogy huzamos és ismételt lenyelése esetén károsítja a szervezetet (vese).

H315 Bőrirritáló hatású.

H318 Súlyos szemkárosodást okoz.

H400 Nagyon mérgező a vízi élővilágra.

H411 Mérgező a vízi élővilágra, hosszan tartó károsodást okoz.

H317 Allergiás bőrreakciót válthat ki.

EUH208 <Allergén anyag neve>-t tartalmaz. Allergiás reakciót válthat ki

H330 Belélegezve halálos.

H310 Bőrrel érintkezve halálos.

H301 Lenyelve mérgező

H314 Súlyos égési sérülést és szemkárosodást okoz.

H410 Nagyon mérgező a vízi élővilágra, hosszan tartó károsodást okoz.

EUH071 Maró hatású a légutakra

H319 Súlyos szemirritációt okoz.

Veszélyességi osztály és veszélyességi kategória	Kód	Leírás
Acute Tox. 2	3.1/2/Dermal	Akut toxicitás (bőrön át), kategória 2
Acute Tox. 2	3.1/2/Inhal	Akut toxicitás (belélegzéssel), kategória 2
Acute Tox. 3	3.1/3/Oral	Akut toxicitás (szájon át), kategória 3

Biztonsági adatlap.
WIZZY RINNOVA PELLE



Acute Tox. 4	3.1/4/Oral	Akut toxicitás (szájon át), kategória 4
Skin Corr. 1C	3.2/1C	Bőrmarás, kategória 1C
Skin Irrit. 2	3.2/2	Bőrirritáció, kategória 2
Eye Dam. 1	3.3/1	Súlyos szemkárosodás, kategória 1
Eye Irrit. 2	3.3/2	Szemirritáció, kategória 2
Skin Sens. 1	3.4.2/1	Bőrszenzibilizáció, kategória 1
Skin Sens. 1A	3.4.2/1A	Bőrszenzibilizáció, kategória 1A
STOT RE 2	3.9/2	Célszervi toxicitás – ismétlődő expozíció, Kategória 2
Aquatic Acute 1	4.1/A1	Akut vízi toxicitási veszély, Kategória 1
Aquatic Chronic 1	4.1/C1	Krónikus (hosszú távú) vízi toxicitási veszély, Kategória 1
Aquatic Chronic 2	4.1/C2	Krónikus (hosszú távú) vízi toxicitási veszély, Kategória 2

Az előző kiadás módosított bekezdései:

- 2. SZAKASZ: A veszély azonosítása
- 3. SZAKASZ: Összetétel vagy az összetevőkre vonatkozó adatok
- 4. SZAKASZ: Elsősegély-nyújtási intézkedések
- 7. SZAKASZ: Kezelés és tárolás
- 8. SZAKASZ: Az expozíció elleni védekezés/egyéni védelem
- 11. SZAKASZ: Toxikológiai adatok
- 12. SZAKASZ: Ökológiai adatok
- 15. SZAKASZ: Szabályozással kapcsolatos információk
- 16. SZAKASZ: Egyéb információk

Ezt a dokumentumot olyan szakember készítette, aki ezzel kapcsolatban megfelelő képzést kapott
Főbb bibliográfiai források:

ECDIN – Vegyi anyagok környezetvédelmi adat- és információs hálózata – Közös Kutatóközpont,
az Európai Közösségek Bizottsága
SAX: AZ IPARI ANYAGOK VESZÉLYES TULAJDONSÁGAI – Nyolcadik kiadás – Van Nostrand
Reinold

A közzétett információk a fent jelzett időpontban rendelkezésünkre álló ismeretekre alapulnak.
Kizárólag a megjelölt termékre vonatkoznak és nem képeznek különösebb minőségi garanciát.
A felhasználónak kötelessége megbizonyosodni ezen információk helyessége és teljessége felől, az
egyéni felhasználásnak megfelelően.

Ez az adatlap minden előzetes adatlapot érvénytelenít és helyettesít.

ADR: Veszélyes Áruk Nemzetközi Közúti Szállításáról szóló Európai
Megállapodás.
ATE: Becsült akut toxicitási érték
ATEmix: Akut toxicitási érték (Keverékek)
CAS: Kémiai Nyilvántartó Szolgálat (az Amerikai Kémiai Társaság részlege).
CLP: Oszályozás, Címkézés, Csomagolás.

Biztonsági adatlap. WIZZY RINNOVA PELLE



DNEL:	Származtatott hatásmentes szint.
EINECS:	Létező Kereskedelmi Vegyi Anyagok Európai Jegyzéke.
GefStoffVO:	Veszélyes Anyagok Német Szabályzata.
GHS:	Vegyi Anyagok Osztályozásának és Címkézésének Egyetemes Harmonizált Rendszere.
IATA:	Nemzetközi Légiszállítási Szövetség.
IATA-DGR:	Nemzetközi Légiszállítási Szövetség - Veszélyes Anyagok Előírásai.
ICAO:	Nemzetközi Polgári Repülési Szervezet.
ICAO-TI:	Nemzetközi Polgári Repülési Szervezet Műszaki Utasítása.
IMDG:	Veszélyes Áruk Nemzetközi Tengerészeti Kódexe.
INCI:	A Kozmetikai Összetevők Nemzetközi Nevezéktana.
KSt:	Robbanási együttható.
LC50:	Közepes halálos koncentráció
LD50:	Közepes halálos dózis
NA:	Nem alkalmazható
PNEC:	Becsült Hatásmentes Koncentráció
RID:	Veszélyes Áruk Nemzetközi Vasúti Fuvarozásáról szóló Szabályzat
STEL:	Rövid Távú Expozíciós Érték
STOT:	Célszervi Toxicitás.
TLV:	Küszöbérték.
TWA:	Időarányosan súlyozott átlag
WGK:	Vízveszélyeztetési osztály.

Exposure Scenario, 19/07/2019

Substance identity	
Chemical name	ETHYLENE GLYCOL
CAS No.	107-21-1
EINECS No.	203-473-3

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Widespread use by professional workers
4. **ES 4** Consumer use; Various products (PC9a, PC1, PC4, PC8, PC15)

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1
CS3 Industrial	PROC2
CS4 Industrial	PROC3
CS5 Industrial	PROC4
CS6 Industrial	PROC8b
CS7 Industrial	PROC7
CS8 Industrial	PROC8a
CS9 Industrial	PROC10
CS10 Industrial	PROC13

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

1.2. CS2: Worker Contributing Scenario: Industrial (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS3: Worker Contributing Scenario: Industrial (PROC2)

Process Categories

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS4: Worker Contributing Scenario: Industrial (PROC3)

Process Categories

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS5: Worker Contributing Scenario: Industrial (PROC4)

Process Categories

Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS6: Worker Contributing Scenario: Industrial (PROC8b)**Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS7: Worker Contributing Scenario: Industrial (PROC7)**Process Categories**

Industrial spraying (PROC7)

Product (article) characteristics**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 1 L/min

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 5 days per week

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of: 90 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 1000 m³**1.2. CS8: Worker Contributing Scenario: Industrial (PROC8a)****Process Categories**

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

Ventilation rate: > 90 %

1.2. CS9: Worker Contributing Scenario: Industrial (PROC10)

Process Categories

Roller application or brushing (PROC10)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

1.2. CS10: Worker Contributing Scenario: Industrial (PROC13)

Process Categories

Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

1.3 Exposure estimation and reference to its source

1.3. CS2: Worker Contributing Scenario: Industrial (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.001
inhalative, local, long-term	N/A	EASY TRA v2.0	0.001
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.004

1.3. CS3: Worker Contributing Scenario: Industrial (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.07
inhalative, local, long-term	N/A	EASY TRA v2.0	0.07
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.08

1.3. CS4: Worker Contributing Scenario: Industrial (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.22
inhalative, local, long-term	N/A	EASY TRA v2.0	0.22
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.223

1.3. CS5: Worker Contributing Scenario: Industrial (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS6: Worker Contributing Scenario: Industrial (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37

inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS7: Worker Contributing Scenario: Industrial (PROC7)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.28
inhalative, local, long-term	N/A	EASY TRA v2.0	0.28
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.52
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.8

1.3. CS8: Worker Contributing Scenario: Industrial (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS9: Worker Contributing Scenario: Industrial (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.03
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.77

1.3. CS10: Worker Contributing Scenario: Industrial (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01

combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.75
--------------------------------------	-----	---------------	------

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers

2.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC3
CS5 General use from professional operators	PROC4
CS6 General use from professional operators	PROC8b
CS7 General use from professional operators	PROC8a
CS8 General use from professional operators	PROC10
CS9 General use from professional operators	PROC11
CS10 General use from professional operators	PROC13

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)**Process Categories**

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)**Process Categories**

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Process Categories Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Process Categories Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS7: Worker Contributing Scenario: General use from professional operators (PROC8a)

Process Categories Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %**2.2. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)****Process Categories**

Roller application or brushing (PROC10)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Wear suitable respiratory protection.

Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %**2.2. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)****Process Categories**

Non industrial spraying (PROC11)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 0.05 L/min

Duration:

Exposure duration 180 min

Frequency:

Use frequency < 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374. Use suitable eye protection.	Inhalation - minimum efficiency of: 90 %
Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 100 m³

Ventilation rate: 80 %

2.2. CS10: Worker Contributing Scenario: General use from professional operators (PROC13)

Process Categories Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency < 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374. Use suitable eye protection.	Inhalation - minimum efficiency of: 90 %
---	--

Other conditions affecting worker exposure

Indoor use

2.3 Exposure estimation and reference to its source

2.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.001
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.001
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.003

dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.004
-----------------------------	-----	------------------------	-------

2.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.01
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.38

2.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.22
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.22
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.003
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.223

2.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.006
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.8

2.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.06
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.8

2.3. CS7: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.13
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.5

2.3. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.3
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.4

2.3. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.4
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.4
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.51
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.91

2.3. CS10: Worker Contributing Scenario: General use from professional operators (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.01
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.75

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Widespread use by professional workers

3.1 TITLE SECTION

Exposure Scenario name	Use in antifreeze products
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8d
----------------	-------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC8a
CS5 General use from professional operators	PROC8b
CS6 General use from professional operators	PROC11

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

3.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

3.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Process Categories

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

3.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC8a)

Process Categories

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear suitable respiratory protection.

Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %

3.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC8b)

Process Categories

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

3.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC11)

Process Categories

Non industrial spraying (PROC11)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Exposure duration 180 min

Frequency:

Covers exposure up to 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of: 90 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 100 m³

3.3 Exposure estimation and reference to its source

3.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.001
inhalative, local, long-term	N/A	EASY TRA v2.0	0.001
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003

combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.004
--------------------------------------	-----	---------------	-------

3.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.38

3.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.13
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.5

3.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.8

3.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.4
inhalative, local, long-term	N/A	EASY TRA v2.0	0.4
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.51
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.91

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Consumer use; Various products (PC9a, PC1, PC4, PC8, PC15)

4.1 TITLE SECTION

Exposure Scenario name	Consumer goods
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Non-metal surface treatment products (PC15) - Heat transfer fluids (PC16) - Hydraulic fluids (PC17) - Ink and toners (PC18) - Leather treatment products (PC23) - Polishes and wax blends (PC31) - Polymer preparations and compounds (PC32) - Textile dyes and impregnating products (PC34) - Washing and cleaning products (PC35)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8c - ERC8d - ERC8f - ERC9a - ERC9b
-----------------------	---

Consumer Contributing Scenario

CS2 Consumer	PC1
CS3 Consumer	PC4 - PC16 - PC17 - PC4_1
CS4 Consumer	PC4 - PC4_2
CS5 Consumer	PC9a - PC15 - PC9a_2, PC15_2
CS6 Consumer	PC8
CS7 Consumer	PC18
CS8 Consumer	PC31
CS9 Consumer	PC32
CS10 Consumer	PC35 - PC8_2, PC35_2
CS11 Consumer	PC35 - PC8_3, PC35_3
CS12 Consumer	PC15 - PC23 - PC34 - PC9a_1, PC15_1

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8c, ERC8d, ERC8f, ERC9a, ERC9b)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use leading to inclusion into/onto article (indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) - Widespread use leading to inclusion into/onto article (outdoor) - Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC8a, ERC8c, ERC8d, ERC8f, ERC9a, ERC9b)
---	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

4.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Product Categories	Adhesives, sealants (PC1)
---------------------------	---------------------------

<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 0.75 %	
4.2. CS3: Consumer Contributing Scenario: Consumer (PC4, PC16, PC17)	
Product Categories	Anti-freeze and de-icing products - Heat transfer fluids - Hydraulic fluids (PC4, PC16, PC17)
Product (Sub-)Categories	Washing car window (PC4_1)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 45 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Exposure duration < 15 min	
4.2. CS4: Consumer Contributing Scenario: Consumer (PC4)	
Product Categories	Anti-freeze and de-icing products (PC4)
Product (Sub-)Categories	Pouring into radiator (PC4_2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
4.2. CS5: Consumer Contributing Scenario: Consumer (PC9a, PC15)	
Product Categories	Coatings and paints, thinners, paint removers - Non-metal surface treatment products (PC9a, PC15)
Product (Sub-)Categories	Solvent rich, high solid, water borne paint (PC9a_2, PC15_2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 10 %	
4.2. CS6: Consumer Contributing Scenario: Consumer (PC8)	
Product Categories	Biocidal products (PC8)
4.2. CS7: Consumer Contributing Scenario: Consumer (PC18)	
Product Categories	Ink and toners (PC18)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
4.2. CS8: Consumer Contributing Scenario: Consumer (PC31)	
Product Categories	Polishes and wax blends (PC31)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 10 %	
4.2. CS9: Consumer Contributing Scenario: Consumer (PC32)	
Product Categories	Polymer preparations and compounds (PC32)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
4.2. CS10: Consumer Contributing Scenario: Consumer (PC35)	

Product Categories	Washing and cleaning products (PC35)
Product (Sub-)Categories	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) (PC8_2, PC35_2)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 20 %

4.2. CS11: Consumer Contributing Scenario: Consumer (PC35)

Product Categories	Washing and cleaning products (PC35)
Product (Sub-)Categories	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (PC8_3, PC35_3)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

4.2. CS12: Consumer Contributing Scenario: Consumer (PC15, PC23, PC34)

Product Categories	Non-metal surface treatment products - Leather treatment products - Textile dyes and impregnating products (PC15, PC23, PC34)
Product (Sub-)Categories	Waterborne latex wall paint (PC9a_1, PC15_1)

4.3 Exposure estimation and reference to its source

4.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.59
dermal, systemic, long-term	N/A	N/A	0.005
combined routes, systemic, long-term	N/A	N/A	0.505

4.2. CS3: Consumer Contributing Scenario: Consumer (PC4, PC16, PC17)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.28
dermal, systemic, long-term	N/A	N/A	0.08
combined routes, systemic, long-term	N/A	N/A	0.36

4.2. CS4: Consumer Contributing Scenario: Consumer (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0
dermal, systemic, long-term	N/A	N/A	0.09
combined routes, systemic, long-term	N/A	N/A	0.09

4.2. CS5: Consumer Contributing Scenario: Consumer (PC9a, PC15)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.04
dermal, systemic, long-term	N/A	N/A	0.02
combined routes, systemic, long-term	N/A	N/A	0.06

4.2. CS6: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0
dermal, systemic, long-term	N/A	N/A	0.006
combined routes, systemic, long-term	N/A	N/A	0.006

4.2. CS7: Consumer Contributing Scenario: Consumer (PC18)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.18
dermal, systemic, long-term	N/A	N/A	0
combined routes, systemic, long-term	N/A	N/A	0.18

4.2. CS8: Consumer Contributing Scenario: Consumer (PC31)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.56
dermal, systemic, long-term	N/A	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.6

4.2. CS9: Consumer Contributing Scenario: Consumer (PC32)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.009
dermal, systemic, long-term	N/A	N/A	0.001
combined routes, systemic, long-term	N/A	N/A	0.01

4.2. CS10: Consumer Contributing Scenario: Consumer (PC35)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.09
dermal, systemic, long-term	N/A	N/A	0.22
combined routes, systemic, long-term	N/A	N/A	0.31

4.2. CS11: Consumer Contributing Scenario: Consumer (PC35)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.02
dermal, systemic, long-term	N/A	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.022

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.